

# TOMWOOD

## HOW TO DETERMINE YOUR RING SIZE

### CONFIRM PRINTED PAPER SIZE



1. Ring measurements are very precise. Carefully follow these instructions to obtain an accurate measurement.

2. Prior to printing, ensure that Page Scaling is set to "None" on your print dialog box. (To open the print dialog box, press CTRL+P.)

3. Measure the bar on the left. It must be exactly 1 inch or 30 mm long.

### MEASURE CURRENT RING


1. Select a ring that properly fits the intended finger. Engagement and wedding rings are traditionally worn on the ring finger on the left hand in the both US and Europe.

2. Place the ring over the circles below, matching the inside edge of the ring to the circle nearest in size. This measurement refers to the inside diameter of the ring in mm.

3. If the ring falls between two sizes, order the larger size.

### SIZES

|            |            |            |            |
|------------|------------|------------|------------|
| 15,3<br>48 | 15,9<br>50 | 16,5<br>52 | 17,2<br>54 |
| 17,8<br>56 | 18,5<br>58 | 19,2<br>60 |            |
| 19,8<br>62 | 20,4<br>64 | 21,0<br>66 |            |



MEASUREMENTS MATCH THE  
INSIDE EDGE OF THE RING

MEASUREMENTS REFLECT RING SIZES DIAMETER IN MILLIMETER